

**Feature:**

- > 1/2.9" Megapixels CMOS
- > 25/30fps@720P
- > High speed, long distance real-time transmission
- > HD and standard definition switch
- > Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- > 8mm fixed lens (4mm, 6mm, 12mm optional)
- > Max. 4pcs Array IR LEDs length 60m, Smart IR
- > IP66, DC12V



<b>Model</b>	<b>VC-A703</b>
<b>Camera</b>	
Image Sensor	1/2.9" Megapixels CMOS
Effective Pixels	1280(H)×720(V)
Electronic Shutter	4/25s~1/45,000s ,4/30s~1/54,000s
Video Frame Rate	1280×720@25 fps; 1280×720@30 fps;
Synchronization	Internal
Min. Illumination	0.01Lux@F1.4(0Lux IR LED on)
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)
<b>Camera Features</b>	
Max. IR LEDs Length	60m IR
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	2D/3D
OSD Menu	Optional
<b>Lens</b>	
Focal length	8mm (4mm, 6mm,12mm optional)
Mount Type	CS
<b>General</b>	
Power Supply	DC12V±10%
Power Consumption	650mA(MAX)
Working Environment	-30°C~+60°C/ Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions(W×D×H)	Φ235mm x190x90mm
Weight	1200g
Others	Default: bracket not included